



Spot FIX Specifications

Last Updated: 17 November 2025

Table of Contents

1. Overview	4
2. Version History	4
3. Abaxx Spot	4
4. Abaxx Spot Timings	4
5. OrderTypes and Validity	4
6. SPOT FIX Trading	5
7. FIX Connection Details.....	5
8. Contact Us	5
9. Standard Headers and Trailers	5
9.1 Standard Headers Structure	5
9.2 Standard Trailer Structure	6
10. Session Messages.....	6
10.1 Logon (A)	6
10.2 Heartbeat (0).....	7
10.3 TestRequest (1).....	7
10.4 ResendRequest (2)	7
10.5 Reject (3).....	7
10.6 SequenceReset (4).....	8
10.7 Logout (5)	8
11. Trading Messages	8
11.1 Supported Client Initiated Messages	8
11.2 Supported Exchange Initiated Messages	8
11.3 Order Lifecycle Scenarios.....	9
11.4 NewOrderSingle (D)	9
11.5 Parties Component Block	10
11.6 OrderCancelRequest (F)	11
11.7 OrderCancelReplaceRequest (G)	11
11.8 OrderMassCancelRequest (q)	12
11.9 ExecutionReport (8).....	13
11.10 OrderMassCancelReport (r).....	16
11.11 OrderCancelReject (9).....	16
11.12 BusinessMessageReject (j)	17

Appendix – Sample FIX Messages.....	18
Appendix A – Session Messages.....	18
A.1 Logon Request	18
A.2 Logon Response	18
A.3 Heartbeat	18
A.4 TestRequest.....	18
A.5 TestRequest Response.....	18
A.6 ResendRequest	18
A.7 Reject	18
A.8 SequenceReset	18
A.9 Logout Request	18
A.10 Logout Response	18
Appendix B – Trading Messages.....	19
B.1 NewOrderSingle	19
B.2 OrderCancelRequest	19
B.3 OrderCancelReplaceRequest	19
B.4 OrderMassCancelRequest	19
B.5 ExecutionReport – New	19
B.6 ExecutionReport – Rejected	19
B.7 ExecutionReport – Trade	19
B.8 ExecutionReport – Cancelled	19
B.9 ExecutionReport – Replaced	20
B.10 ExecutionReport – Order Status.....	20
B.11 OrderMassCancelReport – Accepted.....	20
B.12 OrderMassCancelReport – Rejected	20
B.13 OrderCancelReject.....	20
B.14 BusinessMessageReject	20

1. Overview

Welcome to Abaxx Spot FIX API documentation page.

This document will provide you technical guidance in integrating your application to Abaxx Spot platform.

2. Version History

Version	Date	Comment
1.0	14 August 2025	First draft adapted from Exchange, formatted to Spot systems.
1.1	30 September 2025	Draft sent to eXberry for development.
1.2	17 November 2025	Final draft, reviewed for circulation

3. Abaxx Spot

Abaxx Spot facilitates an efficient execution experience for members across the lifecycle of a trade. Market participants can expect:

- Established market controls that limit user error and prescribe price limits to ensure intraday price movements are within "market-acceptable" ranges
- Instant dissemination of market data

Trading members can access Abaxx Spot through our order management system (OMS), or via API through proprietary or ISV OMS solutions.

Order types based on Limit price or time (*i.e. Day, Good Till Cancel, Good Till Date*) are matched by the trading system on a **price-time** priority basis, standardising and ensuring transparency to members on the matching criteria utilised.

4. Abaxx Spot Timings

Abaxx Spot is operating 24/7.

5. OrderTypes and Validity

OrderType/TimeInForce Matrix

Type	DAY	GTC	GTD	FOK	IOC
Limit	✓	✓	✓	✓	✓

Supported Order Types

OrderType	Description
Limit	Order is being sent with a specific price. A buy order will be executed with the requested price or lower price a sell order will be executed with the requested price or higher price.

Supported Order Validity

TimelnForce	Description
DAY	Order will be automatically cancelled when trading day is closed.
GTC	Good Till Cancel (resting on book till cancellation)
GTD	Good Till Date (at given time (expiryDate) order will be automatically cancelled).
FOK	Fill Or Kill (all or nothing)
IOC	Immediate Or Cancelled (allows partial fills)

6. SPOT FIX Trading

The FIX API meant to serve clients with FIX integration knowledge and experience, if this is not the case, it is recommended you use which is easier to integrate.

Abaxx SPOT FIX gateway enables participants:

- **Trading:** Allows to submit orders commands and to receive real-time information on executed trades.
- **Drop Copy:** Receive real time orders activity and trade reports
- **Market Data:** Consume different types of market data

The interface is a point-to-point service based on the technology and industry standards TCP/IP, FIXT and FIX. The session and application event models and messages are based on versions FIXT1.1 and FIX5.0 (SP 2) respectively.

7. FIX Connection Details

Environment	Hostname	Target Port	Description
UAT	fix-gateway.uat.exberry-uat.io	10080	Trading, Market Data & Reporting
PROD	fix.abaxxspot.com	11080	Trading, Market Data & Reporting

8. Contact Us

For queries: operations@abaxxspot.com

9. Standard Headers and Trailers

9.1 Standard Headers Structure

Tag	Name	Required	Description
8	BeginString	Y	FIXT.1.1 (Must be the 1st field in the message)
9	BodyLength	Y	(Must be the 2nd field in the message)

Tag	Name	Required	Description
35	MsgType	Y	(Must be the 3rd field in the message)
49	SenderCompID	Y	Participant's CompID
56	TargetCompID	Y	Exchange' CompID
34	MsgSeqNum	Y	Sequence number
43	PossDupFlag	N	Indicates possible retransmission of message with this sequence number. Supported values: • N = Original transmission • Y = Possible duplicate
52	SendingTime	Y	Time in UTC (microseconds) Format: YYYYMMDD-hh:mm:ss.uuuuuu
122	OrigSendingTime	N	Required if PossDupFlag(43) is set to Y Time the message was originally transmitted in UTC (microseconds) Format: YYYYMMDD-hh:mm:ss.uuuuuu

9.2 Standard Trailer Structure

Tag	Name	Required	Description
10	Checksum	Y	FIX checksum calculated

10. Session Messages

10.1 Logon (A)

Tag	Name	Required	Description
98	EncryptMethod	Y	Supported values: • 0 = None / Other • 99 = Custom
108	HeartBtInt	Y	Always 108 = 30
553	Username	Y	Market participant's apiKey
554	Password	Y	• EncryptMethod(98) = 0 - use market participant's apiKey • EncryptMethod(98) = 99 - use digital signature

Tag	Name	Required	Description
141	ResetSeqNumFlag	N	Supported values: - Y = Reset MsgSeqNum to 1 - N = Do not reset MsgSeqNum
1137	DefaultApplVerID	Y	Always 1137 = 9 (FIX50SP2)
20037	Custom field	N	Supported values: - Y = sending in the ER the information about the legs and the parent trades - N = sending in the ER the information only about the parent trades - If not sent, system will use N as default

10.2 Heartbeat (0)

Tag	Name	Required	Description
112	TestReqID	N	Required when the heartbeat is the result of a TestRequest message. ID of the TestRequest

10.3 TestRequest (1)

Tag	Name	Required	Description
112	TestReqID	N	ID of the TestRequest

10.4 ResendRequest (2)

Tag	Name	Required	Description
7	BeginSeqNo	Y	MsgSeqNum of first message in range to be resent
16	EndSeqNo	Y	MsgSeqNum of last message in range to be resent. - If the request is for partial resends it will contain the last missed message sequence number. - If request is for all messages subsequent to a particular message, EndSeqNo = 0 (representing infinity).

10.5 Reject (3)

Tag	Name	Required	Description
98	RefSeqNum	Y	MsgSeqNum of rejected message
58	Text	N	Error message
373	SessionRejectReason	N	Error Code as per FIX specifications
371	RefTagID	N	Reference TagID caused the rejection

Tag	Name	Required	Description
372	RefMsgType	N	Reference MsgType of rejected message

10.6 SequenceReset (4)

Tag	Name	Required	Description
123	GapFillFlag	N	Indicates that the SequenceReset message is replacing administrative or application messages which will not be resent. <i>Supported values:</i> N = SequenceReset - Ignore MsgSeqNum(34) Y = Gap Fill Message - MsgSeqNum(34) is valid Exchange sends out only Y as part of the ResendRequest flow. In case client application will send message with N, Exchange will ignore the MsgSeqNum(34) and apply the NewSeqNo(36) as the new inbound sequence

10.7 Logout (5)

Tag	Name	Required	Description
58	Text	N	Free text

11. Trading Messages

11.1 Supported Client Initiated Messages

Message	MsgType	Usage
NewOrderSingle	D	Allows the MP to submit a new order
OrderCancelRequest	F	Allows the MP to cancel an active order
OrderCancelReplaceRequest	G	Allows the MP to modify an active order
OrderMassCancelRequest	q	Allows the MP to mass cancel all active orders for a specific instrument

11.2 Supported Exchange Initiated Messages

Message	MsgType	Usage
ExecutionReport	8	Indicates the result of order command.
OrderMassCancelReport	r	Indicates the result of the mass cancel command.
OrderCancelReject	9	Indicates that an order cancel request or order cancel/replace request has been rejected.

Message	MsgType	Usage
BusinessMessageReject	j	Indicates that an application message could not be processed

11.3 Order Lifecycle Scenarios

Below scenarios summarize the trading actions that are support with the corresponded **ExecutionReport**.

Scenario	ExecType(150)	OrdStatus(39)
Order Rejected	8 (<i>Rejected</i>)	8 (<i>Rejected</i>)
Order accepted and order is fully resting on the book	0 (<i>New</i>)	0 (<i>New</i>)
Order accepted and order is fully executed immediately	F (<i>Trade</i>)	2 (<i>Filled</i>)
Order accepted and order is partially executed immediately, and the residual is resting on the book	F (<i>Trade</i>)	1 (<i>Partially filled</i>)
Order accepted and order is partially executed immediately, and the residual is cancelled (IOC)	F (<i>Trade</i>) & 4 (<i>Cancelled</i>)	1 (<i>Partially filled</i>) & 4 (<i>Cancelled</i>)
Order with immediate TIF (IOC, FOK) that failed to be executed	4 (<i>Cancelled</i>)	4 (<i>Cancelled</i>)
GTD order that has expired	4 (<i>Cancelled</i>)	4 (<i>Cancelled</i>)
Order cancelled	4 (<i>Cancelled</i>)	4 (<i>Cancelled</i>)
Order modified	5 (<i>Replaced</i>)	0 (<i>New</i>) or 1 (<i>Partially filled</i>)
Order replaced	4 (<i>Cancelled</i>) & 5 (<i>Replaced</i>)	4 (<i>Cancelled</i>) & 0 (<i>New</i>)

11.4 NewOrderSingle (D)

Tag	Name	Required	Description
11	ClOrdID	Y	Unique identifier for order - Unique per instrument - Growing integer value, MAX: 9223372036854775807 - i.e., use epoch timestamp in nanoseconds to guarantee uniqueness over time
55	Symbol	Y	Symbol

Tag	Name	Required	Description
1	Account	N	Symbol Account mnemonic as agreed between buy and sell sides.
54	Side	Y	Supported values: 1 = Buy 2 = Sell
38	OrderQty	Y	Quantity
40	OrdType	Y	Supported values: 2 = Limit
44	Price	N	Order price. Required for limit orders
59	TimelnForce	Y	Supported values: 0 = DAY 1 = GTC 3 = IOC 4 = FOK 6 = GTD
432	ExpireDate	N	Expiry time in seconds in UTC, required if TimelnForce = GTD and ExpireTime(126) is not specified. Format: YYYYMMDD
126	ExpireTime	N	Expiry time in seconds in UTC, required if TimelnForce = GTD and ExpireDate(432) is not specified. Format: YYYYMMDD-hh:mm:ss
•	Parties Component Block	N	Party information related to the submitter of the request.
110	MinQty	N	Minimum quantity of an IOC order to be executed.

11.5 Parties Component Block

Tag	Name	Required	Description
453	NoPartyIDs	N	Number of parties.
→ 448	PartyID	N	Identification of the party.
→ 447	PartyIDSource	N	Used to identify the classification source. Supported values: P = Proprietary/Custom code

Tag	Name	Required	Description
→ 452	PartyRole	N	Identifies the type of PartyID(448) . Mandatory values: 24 = Customer Account Optional values: - Other = Value will be store and forward, only Customer Account (24) is required for booking trades

11.6 OrderCancelRequest (F)

Tag	Name	Required	Description
37	OrderID	N	Order Id to be cancelled Mandatory if OrigClOrdID was not specified
41	OrigClOrdID	N	Original ClOrdID to be cancelled Mandatory if ClOrdID was not specified
11	ClOrdID	Y	Unique ID of cancel request, numbers only
55	Symbol	Y	Symbol

11.7 OrderCancelReplaceRequest (G)

Tag	Name	Required	Description
37	OrderID	Y	Order Id to be cancelled Mandatory if OrigClOrdID was not specified
11	ClOrdID	Y	Unique ID of cancel request, numbers only
110	MinQty	N	Allowed only when 59(TIF)= 3(IOC)
55	Symbol	Y	Symbol
54	Side	Y	Side must be equal to the side of original order.
60	TransactTime	Y	Time this request was initiated/released by the trader or trading system.
38	OrderQty	Y	New OrderQty must be less than the original OrderQty
40	OrdType	Y	OrdType must be equal to the OrdType of original order.
44	Price	N	New order Price Required If OrderQty >= LeavesQty of original order

Tag	Name	Required	Description
99	StopPx	N	New order Stop price Required for stop orders and stop limit orders
59	TimeInForce	N	New order Time In Force Values same as New Order Single
432	ExpireDate	N	Expiry Date Format: YYYYMMDD Required if TimeInForce = GTD and ExpireTime(126) is not specified.
126	ExpireTime	N	New order Expiry time in seconds(UTC Time). Format: YYYYMMDD-hh:mm:ss Required if TimeInForce = GTD and ExpireDate(432) is not specified.

11.8 OrderMassCancelRequest (q)

Tag	Name	Required	Description
11	ClOrdID	Y	Unique ID of cancel request, numbers only
55	Symbol	Y	Symbol
530	MassCancelRequestType	Y	1 = Cancel orders for a security
1461	NoTargetPartyIDs	N	Identifies the number of target parties identified in a mass action.
→ 1462	TargetPartyID	N	Required if NoTargetPartyIDs(1461) > 0 . Used to identify the party targeted for the action specified in the message.
→ 1463	TargetPartyIDSource	N	Required if NoTargetPartyIDs(1461) > 0 . Used to identify source of target party identifier.
→ 1464	TargetPartyRole	N	Required if NoTargetPartyIDs(1461) > 0 . Used to identify the role of source party identifier.

11.9 ExecutionReport (8)

Tag	Name	Required	Description
37	OrderID	Y	Order Id. In case of rejection message will be -1
41	OrigClOrdID	N	ClOrdID of the cancelled/modified order in case ExecType(150) is: 4 = Cancelled

Tag	Name	Required	Description
			5 = Replaced
11	ClOrdID	N	ClOrdID of the request message in case ExecType(150) is: 4 = Cancelled 5 = Replaced 8 = Rejected <i>(In case request is done not from FIX GW it will not be returned)</i> ClOrdID of the order in case ExecType(150) is: 0 = New F = Trade I = Order Status
17	ExecID	Y	Unique identifier of execution report 0 = Case of OrderMassStatusRequest(AF) response
880	TrdMatchID	N	Match Id - only in case ExecType = Trade
150	ExecType	Y	Describes the purpose of the execution report: 0 = New - When order added to the book 4 = Cancelled - When order cancelled from book <i>(also in case of GTD expired)</i> 5 = Replaced - when order was modified 8 = Rejected - When request is rejected F = Trade - When order was executed <i>(Fully or partially)</i> C = Expired - When order is expired I = Order Status - When mass status requested
39	OrdStatus	Y	Current order status (after this message): 0 = New - For success new/ modified order that is fully resting on the book 1 = PartiallyFilled - For partially executed order 2 = Filled - For fully executed order 4 = Cancelled - For success cancel order, also in case of GTD expired 8 = Rejected - For failure to place order
636	WorkingIndicator	N	Applicable only when OrdStatus=0(New) and 1 of the below: - Order is suspended or - Order is triggered. (i.e. Stop/Stop Limit order) and fully resting on the book Y = Order is triggered N = Order is suspended

Tag	Name	Required	Description
58	Text	N	In case of rejection, specifies the error message
103	OrdRejReason	N	In case of rejection, specifies the exchange error code
38	OrderQty	N	Order original quantity
14	CumQty	N	Order total filled quantity
151	LeavesQty	N	Remaining open quantity
32	LastQty	N	Executed amount on current fill only
31	LastPx	N	Executed price on current fill only
55	Symbol	N	Symbol
54	Side	N	Supported values: • 1 = Buy • 2 = Sell Note: On Rejected message will always be 1(Buy)
40	OrdType	N	Supported values: • 2 = Limit
44	Price	N	Order price
59	TimeInForce	N	Supported values: • 0 = DAY • 1 = GTC • 3 = IOC • 4 = FOK • 6 = GTD
432	ExpireDate	N	Expiry Date Format: YYYYMMDD
126	ExpireTime	N	Expiry time in UTC Format: YYYYMMDD-hh:mm:ss
•	Parties Component Block	N	Party information related to the submitter of the request.
912	LastRptRequested	N	Will be included only in case ExecType(150) = I (Order Status) Identify if this is the last record • Y = for the last record • N = for all the rest

Tag	Name	Required	Description
584	MassStatusReqID	N	Will be included only in case ExecType(150) = I (<i>Order Status</i>), from request
110	MinQty	N	Minimum quantity of an order to be executed.
442	MultiLegReportingType	N	Will be shown for strategy trades only if in LOGON(A) → 20037 = Y 1 - Single security - not strategy trade 2 - Individual leg of a multi-leg security 3 - Multi-leg security - the parent trade of multi-leg security
820	TradeLinkID	N	Only if in LOGON(A) → 20037 = Y Only when MultiLegReportingType(442) = 2, will show Parent trade ID (multiLegStrategyTradeId in WS API) (this can be associated with strategy ExecutionReport TrdMatchID(880) of the parent)
1647	NoRelatedInstruments	N	Only if in LOGON(A) → 20037 = Y Only when MultiLegReportingType(442) = 2, shows number of related instruments Will always be 1
1648	RelatedInstrumentType	N	Required if NoRelatedInstruments > 0 The type of instrument relationship 99 (Custom: Multi-leg security)
1649	RelatedSymbol	N	Required if NoRelatedInstruments > 0 Parent Symbol (This is required in order to know explicitly which strategy trade is the parent trade).
1650	RelatedSecurityID	N	Required if NoRelatedInstruments > 0 Parent instrumentId
1651	RelatedSecurityIDSource	N	Required if NoRelatedInstruments > 0 Identifies class or source of the RelatedSecurityID (1650) value. 99 (Custom)

11.10 OrderMassCancelReport (r)

Tag	Name	Required	Description
11	ClOrdID	Y	Unique ID of mass cancel request
530	MassCancelRequestType	Y	1 = Cancel orders for a security

Tag	Name	Required	Description
531	MassCancelResponse	Y	Supported values: 0 = Cancel request rejected 1 = Cancel request succeeded
532	MassCancelRejectReason	N	In case of reject, specify the exchange error code
533	TotalAffectedOrders	N	In case of success, number of orders affected from the mass cancel request
1369	MassActionReportID	Y	Unique ID of mass cancel request
1461	NoTargetPartyIDs	N	Should be populated with the values provided on the associated OrderMassCancelRequest(MsgType=0) . Repeating group below should contain unique combinations of - TargetPartyID - TargetPartyIDSource - TargetPartyRole.
→ 1462	TargetPartyID	N	Should be populated with the values provided on the associated OrderMassCancelRequest(MsgType=0) .
→ 1463	TargetPartyIDSource	N	Should be populated with the values provided on the associated OrderMassCancelRequest(MsgType=0) .
→ 1464	TargetPartyRole	N	Should be populated with the values provided on the associated OrderMassCancelRequest(MsgType=0) .
58	Text	N	In case of reject, specify the error message

11.11 OrderCancelReject (9)

Tag	Name	Required	Description
11	ClOrdID	Y	Unique ID of cancel request
37	OrderID	Y	orderId that was sent to be cancelled/modified. Always NONE
39	OrdStatus	Y	8 = Rejected
102	CxlRejReason	Y	Specify the error code
434	CxlRejResponseTo	Y	Original request is: 1 = Order cancel request 2 = Order cancel/replace request
58	Text	Y	In case of reject, specify the error message

11.12 BusinessMessageReject (j)

Tag	Name	Required	Description
380	BusinessRejectReason	Y	Specify the error code per FIX specifications
58	Text	Y	Specify the error message
45	BusinessRejectReason	Y	Reference msgSeqNum
372	RefMsgType	Y	The MsgType(35) of the FIX message being referenced

Appendix – Sample FIX Messages

Appendix A – Session Messages

A.1 Logon Request

8=FIXT.1.1|9=199|35=A|34=1|49=FIRM|52=20230413-07:04:45.549606|56=ABAXXSPOT|553=USERNAME|554=PASSWORD|20037=Y|98=0|108=30|141=Y|1137=9|10=130|

A.2 Logon Response

8=FIXT.1.1|9=89|35=A|34=1|49=ABAXXSPOT|52=20230413-07:04:45.823352|56=FIRM|98=0|108=30|141=Y|1137=9|10=245|

A.3 Heartbeat

8=FIXT.1.1|9=64|35=0|34=2|49=FIRM|52=20230413-08:08:17.710123|56=ABAXXSPOT|10=080|

A.4 TestRequest

8=FIXT.1.1|9=73|35=1|34=6|49=FIRM|52=20230413-08:09:52.868580|56=ABAXXSPOT|112=TEST|10=124|

A.5 TestRequest Response

8=FIXT.1.1|9=73|35=0|34=6|49=ABAXXSPOT|52=20230413-08:09:52.899403|56=FIRM|112=TEST|10=121|

A.6 ResendRequest

8=FIXT.1.1|9=75|35=2|34=33|49=FIRM|52=20230413-08:23:03.597499|56=ABAXXSPOT|7=20|16=0|10=073|

A.7 Reject

8=FIXT.1.1|9=113|35=5|34=3|49=FIRM|52=20230414-02:19:18.649517|56=ABAXXSPOT|58=MsgSeqNum too low, expecting 2 but received 1|10=040|

A.8 SequenceReset

8=FIXT.1.1|9=72|35=4|49=FIRM|56=ABAXXSPOT|34=448|52=20230414-02:21:20.868575|36=445|123=Y|10=097|

A.9 Logout Request

8=FIXT.1.1|9=91|35=5|34=6|49=ABAXXSPOT|52=20230414-02:22:16.569898|56=FIRM|58=Client initiated logout|10=013|

A.10 Logout Response

8=FIXT.1.1|9=64|35=5|34=7|49=FIRM|52=20230414-02:22:16.520312|56=ABAXXSPOT|10=079|

Appendix B – Trading Messages

B.1 NewOrderSingle

8=FIXT.1.1|9=157|35=D|34=6|49=FIRM|52=20230417-
06:35:50.551725|56=ABAXXSPOT|11=1681713329128057|38=5|40=2|44=3.6|54=1|55=AUSINK99|59=1|
453=1|448=CL00001|447=D|452=24|10=007|

B.2 OrderCancelRequest

8=FIXT.1.1|9=114|35=F|34=7|49=FIRM|52=20230417-
06:40:02.668041|56=ABAXXSPOT|11=1681713593666681|41=1681713552808524|55=AUSINK99|10=16
3|

B.3 OrderCancelReplaceRequest

8=FIXT.1.1|9=105|35=G|34=3|49=FIRM|52=20230417-
06:54:41.810225|56=ABAXXSPOT|11=1681714468232072|37=18|38=5|55=AUSINK99|10=156|

B.4 OrderMassCancelRequest

8=FIXT.1.1|9=101|35=q|34=10|49=FIRM|52=20230417-
06:57:45.588953|56=ABAXXSPOT|11=1681714584168715|55=AUSINK99|530=1|10=046

B.5 ExecutionReport – New

8=FIXT.1.1|9=259|35=8|34=27|49=ABAXXSPOT|52=20230417-
07:02:36.984844|56=FIRM|11=1681714928236006|14=0|17=27490|37=21|38=5|39=0|40=2|44=3.60|54
=1|55=AUSINK99|59=1|60=20230417-
07:02:36.977804|150=0|151=5|453=2|448=CL00001|447=D|452=7|448=CL00001|447=D|452=710=00
0|

B.6 ExecutionReport – Rejected

8=FIXT.1.1|9=152|35=8|49=ABAXXSPOT|56=MP1|34=4|52=20230417-
07:18:08.839269|17=27520|150=8|37=-
1|11=1681715386652710|39=8|103=1011|54=1|14=0|151=0|58=Permission denied for this
instrument|10=037|

B.7 ExecutionReport – Trade

8=FIXT.1.1|9=280|35=8|34=6|49=ABAXXSPOT|52=20230417-
07:10:10.115812|56=FIRM|11=1681715386652704|14=2|17=27509|31=4.50|32=2|37=2|38=2|39=2|40=1|5
4=2|55=RD1Z24|59=4|60=20230417-
07:10:10.107444|75=20230417|150=F|151=0|453=2|448=CL00001|447=D|452=7|448=CL00001|447=D
|452=7|880=1|10=147|

B.8 ExecutionReport – Cancelled

8=FIXT.1.1|9=279|35=8|34=18|49=ABAXXSPOT|52=20230417-
07:14:44.047668|56=FIRM|11=1681715678264620|14=0|17=27518|37=4|38=10|39=4|40=2|41=16817156
03111519|44=3.50|54=1|55=RD1Z24|59=1|60=20230417-
07:14:44.042350|150=4|151=0|453=2|448=CL00001|447=D|452=7|448=CL00001|447=D|452=7|10=19
6|

B.9 ExecutionReport – Replaced

8=FIXT.1.1|9=280|35=8|34=21|49=ABAXXSPOT|52=20230417-
07:16:11.384506|56=FIRM|11=1681715762541856|14=0|17=27520|37=5|38=10|39=0|40=2|41=1681715712
522661|44=10.00|54=2|55=RD1Z24|59=1|60=20230417-
07:16:11.376005|150=5|151=5|453=2|448=CL00001|447=D|452=7|448=CL00001|447=D|452=7|10=222
|

B.10 ExecutionReport – Order Status

8=FIXT.1.1|9=292|35=8|34=2|49=ABAXXSPOT|52=20230417-
07:44:01.110660|56=FIRM|11=1681715712522661|14=0|17=0|31=0|32=0|37=5|38=10|39=0|40=2|44=10.0
0|54=2|55=RD1Z24|59=1|60=20230417-07:16:11.376005|150=1|151=5|453=2|448=C
L00001|447=D|452=7|448=CL00001|447=D|452=7|584=1681717439131833|912=Y|10=245|

B.11 OrderMassCancelReport – Accepted

8=F11XT.1.1|9=139|35=3|34=6|49=FIRM|52=20230417-
07:06:02.144455|56=ABAXXSPOT|45=4|58=Value is incorrect (out of range) for this
tag|371=102|372=9|373=5|10=011|

B.12 OrderMassCancelReport – Rejected

8=FIXT.1.1|9=136|35=r|49=ABAXXSPOT|56=FIRM|34=19|52=20230208-
12:56:07.210122|11=1675860968239|530=1|531=0|532=1010|58=Instrument FIX not
found|1369=41488|10=255|

B.13 OrderCancelReject

8=FIXT.1.1|9=139|35=3|34=6|49=FIRM|52=20230417-
07:06:02.144455|56=ABAXXSPOT|45=4|58=Value is incorrect (out of range) for this
tag|371=102|372=9|373=5|10=011|

B.14 BusinessMessageReject

8=FIXT.1.1|9=280|35=j|49=ABAXXSPOT|56=FIRM|34=2|52=20230417-
06:57:45.642669|45=2|372=x|380=6|58=This apiKey
doesn't have the right permission